


- ① G5 CHRISTY BOX OR APPROVED EQUAL. LID SHALL BE ENTITLED "MONUMENT".
- ② 2½" DIAMETER, SURVEY MARKER SHALL BE LIETZ 8134-16, OR SERVICE COMPANY 287-C. GEODETIC BRASS CAPS SHALL BE 3¼" DIAMETER STAMPED "CITY OF WEST SACRAMENTO" AND "GEODETIC CONTROL SURVEY".
- ③ EXISTING GRADE.
- ④ CLASS "A" CONCRETE.
- ⑤ 1/4" DIAMETER WELDED STEEL CIRCULAR PLATE, 1/8" MAXIMUM LIP.
- ⑥ 4" DIAMETER, 6 FEET LONG SCHEDULE 40 GALVANIZED PIPE.
- ⑦ 3/4" DIAMETER, 10 INCH LONG GALVANIZED ROD.

NOTES:

- A. THE R.C.E. OR L.S. NUMBER MUST APPEAR ON MONUMENT MARKERS.
- B. MARK REFERENCE POINT WITH A PUNCHMARK.
- C. BOLLARD SHALL BE PRIMERED & PAINTED WITH 2 COATS OF WHITE PAINT.
- D. BOLLARD TO BE INSTALLED IN UNIMPROVED AREAS.

THE CITY OF WEST SACRAMENTO – STANDARD DETAIL

APPROVED BY: 	C-38733	3/31/05
CITY ENGINEER	P.E. NO.	DATE
REVISION:		
REVISION:		
REVISION:		
REVISION:		

TITLE:
**SURVEY MONUMENT
 OUTSIDE OF ROADWAY**

STANDARD
 DETAIL #: 244

